		Subaru 3 Spee	d, M41 (4 Pads)	
Ref: SU-1	10", 4 Round Pads			
	1975-79 (Smoo	oth or Dimpled)		Su
	105 T Ring Gear			ba
SU1	Type: Non Lock Up	Hub: No Drive	Contra La Contra Contra	ru 3
501	Diameter: 10"	Input Splines: 18		ရှိ
	Bolt Circle: 9.55"	105 T Ring Gear	Contraction of the second	ee
	Mounting: 4 Pads	Pilot Dia: .630"	and the state of t	Subaru 3 Speed, M41
	Subaru 3	Speed, M41 (4 Tap	ped Holes in Mounting Ring)	
Ref: SU-4	11.5", No Raised Outside Bo	oss, No Extra Ring on Cover		
	1983-Up 4wd Turbo			
	Code: Pink Dot (Some)			
SU4	Clutch Omitted	Hub: No Drive		
	Diameter: 11.5"	Input Splines: 18		6
	Bolt Circle: 10.75"	115 T Ring Gear		
	Mtg: 4 Tapped Holes	Pilot Dia: .630"		l
Ref: SU-5	11.5", No Raised Outside Boss, Extra Ring on Cover]
	1983-Up 4wd Wagon, Loyale		COD AVA	
	Code: White Dot (Can Use SU6)			
SU5	Clutch Omitted	Hub: No Drive		
	Diameter: 11.5"	Input Splines: 18		
	Bolt Circle: 10.75"	115 T Ring Gear		
	Mtg: 4 Tapped Holes	Pilot Dia: .630"]
Ref: SU-6	11.5", No Raised Outside Boss, Extra Ring on Cover]
	1983-Up 4wd Wagon, Loyale			
	Code: Yellow or Orang	e Paint (Can Use SU5)		
SU6	Clutch Omitted	Hub: No Drive		
300	Diameter: 11.5"	Input Splines: 18	Marine Construction of the Desire	
	Bolt Circle: 10.75"	115 T Ring Gear	A REAL PROPERTY OF THE REAL PR	
	Mtg: 4 Tapped Holes	Pilot Dia: .630"]
Ref: SU-2	10.375", .650" Wide Mounting Ring]
	1980-Up (Smooth or Dimpled)			
SU2	115 T Ring Gear			
	Type: Non Lock Up	Hub: No Drive		
	Diameter: 10.375"	Input Splines: 18		
	Bolt Circle: 10.125"	115 T Ring Gear	13333333333333333333333333333333333333	
	Mtg: 4 Tapped Holes	Pilot Dia: .630"		

		ad 8444 (4 Taumad		
Subaru 3 Speed, M41 (4 Tapped			Holes in Mounting Ring) (co	nt.)
Ref: SU-8		", Raised Outside Boss, Extra Ring on Cover		
	1983-Up			·
	Code: Pink Dot (Some)			
SU8	Clutch Omitted	Hub: No Drive		
	Diameter: 11.5"	Input Splines: 18		
	Bolt Circle: 10.75"	115 T Ring Gear		and a state of the
	Mtg: 4 Tapped Holes	Pilot Dia: .630"		
Ref: SU-7	11.5", Raised Outside Boss, No Extra Ring on Cover			
	1983-Up (Can Use SU9)			C. The
	Code: Light Blue or Green Dot			
SU7	Clutch Omitted	Hub: No Drive		NO POST
307	Diameter: 11.5"	Input Splines: 18		
	Bolt Circle: 10.75"	115 T Ring Gear		The state of the second state of the state of the second state of
	Mtg: 4 Tapped Holes	Pilot Dia: .630"		
Ref: SU-9	11.5", Raised Outside Boss, No Extra Ring on Cover			
	1983-Up (Can Use SU7)			070
	Code: Yellow Dot (Some)			
SU9	Clutch Omitted	Hub: No Drive		
509	Diameter: 11.5"	Input Splines: 18		
	Bolt Circle: 10.75"	115 T Ring Gear		THE REAL PROPERTY AND
	Mtg: 4 Tapped Holes	Pilot Dia: .630"		
Ref: SU-10	11.5", .950" Mounting Ring			
	1983-Up			(HI)
	Code: Yellow Dot (Some)			14:11:1
01140	Type: Non Lock Up	Hub: No Drive		
SU10	Diameter: 11.5"	Input Splines: 18		
	Bolt Circle: 11"	115 T Ring Gear		-
	Mtg: 4 Tapped Holes	Pilot Dia: .630"		and the second second second
Ref: SU-14	11.5", No Bosses, Flat Pilot			
	1983-Up			
SU12	Code: Green Dot			((III))
	Type: Lock Up	Hub: No Drive		
	Diameter: 11.5"	Input Splines: 18	Augenter of the and th	
	Bolt Circle: 11"	115 T Ring Gear		And the second s
	Mtg: 4 Tapped Holes	Pilot Dia: .630"		

Pilot Dia: .630"


Mtg: 4 Tapped Holes

		Subaru 4 Speed, E0	C8, R4AX-EL (4EAT)	
Ref: SU-15	10", Narrow Pac	ls, 1.5" Tall Pilot		
SU15	1987-Up			
	Code: 74			
	Type: Lock Up	Hub: Slotted	A Constant of the second secon	
	Diameter: 10"	Input Splines: 23		
	Bolt Circle: 11"	115 T Ring Gear	And and a state in monopolitic and a state of the state o	
	Mounting: 4 Pads	Pilot Dia: .630"		
Ref: SU-11	10.5", Narrow Pads, 1"	Tall Pilot, 11" Bolt Circle		
	1987-Up GLXT, 1990 Legacy Non Turbo			
	Overall Height 5.535"			
01144	Type: Lock Up	Hub: Slotted		
SU11	Diameter: 10.5"	Input Splines: 22		
	Bolt Circle: 11"	115 T Ring Gear	Cardina Contractor States and Contra	
	Mounting: 4 Pads	Pilot Dia: .630"		
Ref: SU-12	10.5", Narrow Pads, 1" Ta	Il Pilot, 11.375" Bolt Circle		
		gacy Turbo		
	-	ight 5.655"		
	Type: Lock Up	Hub: Slotted		
SU13	Diameter: 10.5"	Input Splines: 22		
	Bolt Circle: 11.375"	115 T Ring Gear	The second se	
	Mounting: 4 Pads	Pilot Dia: .630"		
Ref: SU-16	11.125". No Boss	ses, Beveled Pilot		
		II Height 5.650")		
		: 90, 91		
	Type: Lock Up	Hub: Slotted		
SU16	Diameter: 11.125"	Input Splines: 22		
	Bolt Circle: 12"	115 T Ring Gear	A STATE AND A DATE OF A STATE OF A	
	Mtg: 4 Tapped Holes	Pilot Dia: .630"		
Ref: SU-13	11.25". Wide Pa	ads, 1" Tall Pilot		
		Jp SVX		
	Overall Height 5.690"			
	Type: Lock Up	Hub: Slotted		
SU14	Diameter: 11.25"	Input Splines: 22	All I TO I I AND I	
	Bolt Circle: 11.75"	115 T Ring Gear	HILLE CODDAD 2272220	
	Mounting: 4 Pads	Pilot Dia: .630"		
Ref: SU-17	11.25". Wide P	ads, 1.25" Pilot		
		II Height 5.678")		
	Codes: 77, 79			
SU17	Type: Lock Up	Hub: Slotted		
	Diameter: 11.25"	Input Splines: 23		
	Bolt Circle: 11.75"	115 T Ring Gear	A A A A A A A A A A A A A A A A A A A	

Subaru 4 Speed, EC8

Pilot Dia: .630"

Mounting: 4 Pads



No Raised Boss on the Outside? Extra Ring above the Ring Gear, see SU6 & SU5, No Extra Ring, see SU4.